


## CLEANING INSTRUCTIONS - ABS CABINETS

- Our cabinets by are designed to be maintenance free. However, it is recommended that the outer surface of the cabinet, and the hinge area, be kept clear from debris and dirt, to ensure correct operation of the hinged door.
- If latches, locks or hinges need to be lubricated, use a “3 in 1” type light oil, removing excess with a cloth.
- Use a mild solution of detergent and water to clean the surface. Rinse.

 <p><b>ACTIVAR</b> INC. Construction Products Group</p> <p><small>www.activarcpg.com</small></p> <p>JL INDUSTRIES</p>	<h3>CLEANING INSTRUCTIONS - ABS CABINETS</h3>
<p><b>HEADQUARTERS &amp; CUSTOMER SERVICE:</b> 4450 WEST 78<sup>TH</sup> ST CIRCLE, BLOOAINGTON, MN 55435-5416 <b>PH:</b> 800-554-6077 <b>FAX:</b> 952-835-2218 <b>EMAIL:</b> SALES@JLINDUSTRIES.COM WWW.ACTIVARCPG.COM <b>ACPG SOUTHEAST (THOMAS ENTERPRISES):</b> FT MEYERS, FL * <b>ACPG WEST COAST (SAMSON MFG):</b> COMMERCE, CA <b>ACPG WAREHOUSES:</b> DALLAS TX, LANCASTER PA, ATLANTA GA, CHICAGO, IL, SEATTLE WA 1-13-2011</p>	