

FIRE EXTINGUISHER CABINET HANDLE, LOCK & LATCH OPTIONS

ADAC Flush Pull Handle (PRH)

Plastic recessed cup-type handle. Standard on all 4" trim cabinets. Available at additional cost as an option on most cabinets. When the ADAC pull is installed on cabinets with vertical duo door, the window will be on the right-hand side of the cabinet instead of the left, and when installed in a full glass door, the glass size is smaller than with a standard pull. When ordered with a SAF-T-LOK™, the pull is centered top to bottom on the door, to the right of the lock.



Chrome Turn Handle (LH)

Available at additional cost as an option on most cabinets.



Futura Cast FIRE Handle

Cast aluminum. Available at additional cost as an option on most cabinets.

Mill Finish (PUF)

Red Painted (PUFR)

White Painted (PUFW)



Standard Pull Handle

Zinc: Standard on most cabinets. (PUS)

Chrome: Available at additional cost as an option on most cabinets. (P6)

Brass: Available at additional cost as an option on most cabinets.

Brushed Bronze: Available at additional cost as an option on most cabinets.

US10B: Available at additional cost as an option on most cabinets.




SAF-T-LOK™

Theft-deterrent feature with keyed cylinder lock available on most cabinets. Can be used instead of break glass lock lever. In the panic of a fire emergency, the breaking of the glass in a fire extinguisher cabinet door can be dangerous. It creates the possibility of injury to people and serious liability to the building owner. Cabinets with a SAF-T-LOK™ lock appear to be locked and in fact are, but the door can be opened with a sharp pull which breaks the replaceable plastic cam. This deters theft and vandalism which occur from unlocked cabinets and allows quick access to the extinguisher. Plastic cam is 1-5/8" x 1" x 3/32". Extra or replacement cams can be ordered.

The SAF-T-LOK™ cam lock is centered top to bottom on the cabinet door, and can be installed on most door styles with the glazing option you select. Pull handles are installed 3-5/8" inches higher when a SAF-T-LOK™ is installed in your cabinet, except for the ADA recessed pull which is installed to the right of the lock.



Breakable Plastic Cam

| | |
|---|---|
|  <p>ACTIVAR INC. Construction Products Group</p> <p>www.activarcpg.com</p> | FIRE EXTINGUISHER CABINET LOCK & LATCH OPTIONS |
| <p>HEADQUARTERS & MANUFACTURING: 4450 WEST 78TH ST CIRCLE, BLOOMINGTON, MN 55435-5416 ACPG SOUTHEAST (THOMAS ENT): FT MYERS, FL ACPG WEST COAST (SAMSON): COMMERCE, CA WAREHOUSES: DALLAS TX, LANCASTER PA, ATLANTA GA, CHICAGO, IL, SEATTLE WA, PH: 800-554-6077 FAX: 952-835-2218 EMAIL: SALES@JLINDUSTRIES.COM WWW.ACTIVARCPG.COM 8-10-12</p> | |